

## **Rough Terrain Forklift**

Used Rough Terrain Forklift Fresno - Broadly defined, a forklift truck uses two forks to load, transport and unload material. The two main categories of forklifts are industrial forklift and rough terrain forklift. Industrial forklifts are mainly used in loading docks and warehouse applications with smooth and level surfaces. By contrast, the second category of forklifts, rough terrain forklifts, are commonly used to run on uneven and rocky surfaces. Due to size, tires, and weight capacity, a rough terrain lift is primarily used outdoors, often at construction sites. The main difference between industrial and rough terrain forklifts is that industrial forklifts are fitted with cushion tires, a common, over-the-road type tire. Rough terrain forklifts, on the other hand, are fitted with pneumatic tires, a type of tractor tire allowing for better traction and flotation properties. Internal combustion engines can power industrial forklifts; however, more often they rely on an electrical source such as a fuel cell or better. Rough terrain models typically rely on an internal combustion engine.

**Types of Class 7 Rough Terrain Forklift Trucks** There are three main kinds of Class 7 Rough Terrain Forklift Trucks. The rotating telehandler forklift, straight mast forklifts and rotating forklifts are in this category. Every rough terrain forklift truck is designed to operate on disturbed ground and difficult locations commonly found in military and construction atmospheres. The rough terrain models travel and perform well in difficult locations. Safety considerations are taken into account for rough terrain locations with raising loads in difficult environments to keep the operator safe from tipping over. For safety reasons, it is vital the forklift maintains stability before moving, lifting or lowering. Rough terrain forklift operators must practice correct lifting techniques to remain stable on the ground. Straight Mast Forklifts Designed to facilitate safe transport along difficult terrain such as demolition sites and construction locations, straight mast forklifts can complete the job safely and efficiently. Better accessibility and maneuverability are offered by these units thanks to their pneumatic cushion tires. These allow the forklift truck to easily travel over rough terrain on the worksite. It is common for straight mast forklifts to come with 2-wheel or 4-wheel drive. Even though these machines are better utilized in exterior locations, many straight mast forklifts operate with propane or diesel, enabling them to be used indoors for short timeframes. The lift capacities of straight mast forklifts are similar to most standard forklifts with a range of approximately 5,000 to 36,000 pounds.

**Telehandler or Telescopic Handler Forklifts** The distinct telescoping boom on telehandlers and telescopic handler forklifts contribute to the unit's name. This telescoping boom allows the forklift truck to pick up and place loads at various distances and lift heights in front of the machine. Better reachability delivers greater flexibility to the forklift operator while placing loads. Featuring two wheels found at the front and two wheels at the rear, the standard telehandler is a long and low machine. The telescopic boom can be found at the back of the forklift, mounted on a pivot that is attached many feet higher than the frame of the unit. The fuel tank and hydraulic fluid tank are found opposite to the forklifts' cab that is typically mounted on the left side. Within the frame itself, the transmission and engine are located along the center-line of the forklift. This common configuration allows for a balanced forklift which is necessary for the basic stability of the machine which lifting, transporting and lowering loads. Compared to standard forklifts, telehandlers deliver higher lift heights. Otherwise known as high-reach telehandlers or compact telehandlers, these models perform. Compact telehandlers can extend their full load capacity from eight-teen feet and the high-reach models to fifty-six feet. Their load capacities usually range between 5,500 and 12,000 pounds. All-wheel steering is popular for all-terrain forklifts and provides increased maneuverability. Thanks to steering features including power-shift transmission, the operator can maneuver the machine in excellent proximity to the work location. The latest telehandler models feature ergonomic upgrades for ultimate operator comfort. These features include tilted steering options and roomier cabs to increase operator comfort. Increasingly, these types of ergonomic features are in demand at worksites as they have been shown to improve productivity by decreasing operator repetitive stress injuries and operator fatigue. A single joystick is a common design for

most telehandlers. The joystick controls all the forklift's boom functions as well as the hydraulic system which allows for straightforward and efficient operation. These machines can use non-marking tires to allow them to be suitable for maintenance in stadiums and on buildings or billboards and sign operations. Rotating Telehandler or Roto Telescopic Handler Forklifts Rotating telehandler or roto telescopic handler forklifts have many features in common with the standard telehandler forklift. Telehandlers are capable of rotating heavy-lift weights to tremendous heights. This unit's added turntable and rotation flexibility increases the types of jobs it can complete. The rotating function allows the forklift to swivel a full 360 degrees around, enabling access a much larger work area without having to reposition the forklift. With rotating telehandlers, one joystick handles the lift capacity and a second joystick is responsible for the rotation factor. As with the standard telehandler forklift, rotating telehandlers are available with added features including power assist steering, four-wheel drive and minimized slip differential on the rear axle to boost traction and for additional safety. With the added rotating ability of these forklifts, comes additional safety considerations. Stabilizers are a rough terrain forklift feature that rotating telehandler models rely on to increase safety while handling rotating loads that are swinging back and forth from each side of the machine. Certain rotating telehandlers operate without stabilizers; minimizing the time it takes to reposition the machine and move to other workplace locations. Rotator telehandler units are typically smaller than standard telehandlers with their fixed-cab design. Therefore, rotator telehandler units can access smaller loads when compared to standard telehandler units. Load capacities for rotating telehandlers usually range between 4,000 and 10,000 pounds, with lift heights ranging from 15 to 80 feet. Standard and rotator telehandlers can double as a crane when outfitted with specific winch accessories. These units can enable job sites that require a crane to get the job done without having to rent and transport a separate machine. Advancements for Rough Terrain Forklifts Popular rough terrain forklift attachments include rotating fork carriages, booms, articulating booms and winches. Because of the importance of forklift attachments in their ability to adapt forklifts to many different types of specific jobs, it is expected that the creation and availability of new rough terrain forklift attachments will continue to increase. The majority of advancements will be delivered as safety features built to enhance the rough terrain models. Some new safety features have already been developed such as automatic load restriction devices. By automatically weighing a load, these systems calculate the loads' safe reach distance while taking the boom angle and its' extension into account. An alarm sounds once the safe distance is reached, warning the operator to make load weight, reach distance or boom angle adjustments.