

Boomlift / Manlift

Used Boom Lift Fresno - The boom lift is one of the most popular kinds of aerial machinery. Boom lifts go by numerous names including cherry pickers, elevating work platforms, aerial platforms, aerial devices and mobile elevating work platforms; created to conduct jobs at higher elevations. Warehouses, companies, contractors and retail operations and more rely on boom lifts on a daily basis. Keeping workers safe as they access conditions in a higher altitude is priceless. There are numerous models of boom lifts available in the industry. A single operator can control a variety of boom lift models. This machine is popular for harvesting fruit in locations such as orchards that historically relied on climbing dangerous ladders. Ladders need to be secured on solid, even ground in order to be safely accessible, making them hard to rely on in a natural orchard setting. Harvesting fruit is much safer and simpler with a boom lift compared to using a ladder.

Gaining Access Over Obstacles Some boom lift models can move up and over obstacles, making them ideal for working over top of items safely and efficiently. Having the capacity to reach an object even when you are unable to maneuver the equipment directly underneath has a variety of applications including window cleaning, telephone pole and line installation and service, fixing overhead cables and numerous other industries. The articulated boom lift is an example that has numerous joints enabling it to bend over or under items. These sections can independently move to allow workers to gain access to a variety of places. Articulated booms feature a tight turning radius, making them ideal for hallways and narrow storage corridors. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models.

Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. They provide a vital piece to the fleet for servicing power lines and overhead wires. Certain models are outfitted with water cannons to be used in firefighting applications. Maximum reach can be attained with telescoping boom sections on certain models. There are articulating boom lifts complete with an additional jib that allows the platform to extend an extra 6 feet in any direction. Since these machines commonly work on steep ground and rough terrain, they resemble “spiders” with their long legs, and often go by that nickname on the job site. Interior articulating boom lifts are smaller and able to fit through doorways for use inside storage, warehouse and retail capacities. Interior models are typically electric boom lifts due to their lack of dangerous carbon monoxide exhaust and quieter features.

Telescopic Boom Lifts Telescopic boom lifts do not bend the way articulating boom lifts do. These units use hydraulics to retract and extend outwards and upwards. The worker who is in the platform has the controls to extend the lift and is able to operate without a second worker. Certain larger and taller models feature a jib located close to the top similar to an articulating boom lift model. There are models on the market capable of reaching over 180 feet. This equipment has been designed to be reliable and stable, with certain models capable of reaching their extended height in less than a minute. There are diesel and dual-fuel options with adjustable speed and weight range options from five hundred to one thousand pounds. Boom lifts can fit through tiny spaces and there are 4WD options on the market. Telescopic booms are common in a variety of settings due to their ability to combine height and reach.

Jib The jib is the extension found at the end of the main boom and between the platform. This enables extra reach and another articulation point or hinge for the platform to move side-to-side or up-and-down. Jibs are an option on many telescoping and articulating boom lifts. Articulating models have a joint situated roughly halfway between the wheels and the platform to enable it to reach over an obstacle and then lower again if required.

Genie Articulating Boom Lifts A popular type of articulating boom lift manufactured on the market is the Genie Z-boom Model. Designed to provide the most versatility in difficult to access spaces, this model has the capacity to lift up, over and out with superior positioning. The first Genie Z-30/20 articulating Z-boom model was launched in 1985. Thanks to their “up an over” abilities, they have gained the ultimate popularity that continues today.

Proper Safety Measures When operating any type of industrial equipment, safety is

first and foremost. All known safety hazards must be known to anyone working within the vicinity. Operating the equipment safely is vital for the operator and everyone in the vicinity. Before starting the boom lift, it is paramount that the proper safety gear and communication is in place. Prior to operating, ensure there are no open flames, combustible or flammable items, lit cigarettes, battery gases or engine fuels present. For the ultimate safety, it is important to have a visible, safely mounted and accessible fire extinguisher within the operators reach. It is important to maintain a clean work space around charging stations and work surfaces since clutter or tools could puncture tires or damage the machine or its components. Daily Maintenance Daily maintenance includes a visual inspection and consulting the maintenance manual to ensure the machine is up to date and will operate safely. Lifting and supportive devices need to stabilize the weight on hand. Straps, fasteners and chains need to be checked they are in good condition. Single use components and fasteners cannot be reused due to their risk of failure. Discarded solvents and oils must be disposed of safely and in an approved container to prevent environmental contamination. Workbenches and workshop or garage areas need to have adequate lighting and ventilation. Typically the wide umbrella of maintenance is distinguished by subsections such as Commissioning and Programmed Maintenance Intervals, Annual Maintenance, and Quarterly Maintenance. Maintenance Inspection Report The boom lift components are divided and categorized to streamline the process of inspection. Some of the maintenance categories for the boom lift include the Engine, Platform, Controls and Function, Turntable, Booms and Drive Chassis. Not complying with routine maintenance can put the operator at a huge safety risk, lead to damaged components, terrible performance and preventable downtime. The maintenance inspection report extend the performance and service life of the machine and needs to be accurately maintained to ensure the machine is safe to run and that the machine is capable of performing properly. The term commissioning refers to a list of single maintenance procedures that need to be completed at 50- and 150-hour intervals to keep the machine optimally running. There is quarterly and annual maintenance protocol that is conducted once or many times during the year. There are a variety of programmed maintenance procedures based on preparing the machine for pre-delivery machine operating. Consult your maintenance manual prior to operating to ensure all oil changes, battery life and fluid levels are primed for success.